

FLEX-GUARD® Regular Power Black Laser Safety Curtain Barrier **SLC-100W-B**

Page 1 of 1

FLEX-GUARD® Regular Power Black Laser Safety Curtain Barrier, Custom Size, P/N: SLC-100W-B, meets the following certification and compliance standards and is labeled with the following markings:

AATCC TM76
ANSI Z136
ASTM E84
CE EN 12254
CE EN 60825-4
CSFM Title 19 CCR 1237
ISO 14644-1
NFPA-701 TM2
UKCA

Protection Markings

Laser-rated at 120 W/cm² for 100 seconds, wavelength 1070 nm, 1 mm diameter spot (1/e)

D AB8 KTK 190-315 CE
R AB2 KTK 190-315 CE
D AB6 KTK >315-1050 CE
IR AB6 KTK >315-1400 CE
D AB4 KTK >1050-1400 CE
DR AB2 KTK >1400-11100 CE

FLEX-GUARD® products are made in the United States of America.

FLEX-GUARD® REGULAR POWER

Laser Containment Product Series: 100W-B

ANSI Z136, CE EN 12254 and CE EN 60825-4
rated 120W/cm² for 100 seconds, wavelength
1070nm, 1mm diameter spot (1/e).

NFPA-701 TM2, ASTM E84 Standard Methods
of Fire Tests for Flame Propagation of Textiles
and Films, and CSFM Title 19 CCR 1237
(Small Scale) Fire Resistance.



Registration
No.
F-17401




MANUFACTURE DATE

SERIAL NUMBER

5 Jarado Way • Boscawen, NH 03303 • 800.432.2323 • kenteklaserstore.com



Made in the U.S.A.

DAB8 RAB2 KTK 190-315 CE
DAB6 KTK >315-1050 CE
IRAB6 KTK >315-1400 CE
DAB4 KTK >1050-1400 CE
DRAB2 KTK >1400-11100 CE

Representative label, affixed to FLEX-GUARD® Regular Power Black Laser Containment products